Inductive Sensors

BES Q08ZE-NSC20B-BV02

Quadraform 8 x 8
Sn = 2 mm
DC 3-Wire
shielded



PX0670



Utilization categories DC 13

Common Data

Mounting		shielded
Rated operating distance Sn	mm	2,0
Assured operating distance Sa	mm	0...1.6
Repeatability	%	<= 5
Hysteresis	%	<= 15
Function indication		yes
Ambient temperature range	°C	-25...+70
Polution Degree		3
IEC-Code		I1C08AN1
Time delay before availability	ms	<= 10

Mechanical Data

Housing size	mm	Quadraform 8 x 8
Measurements BxHxT or DxT	mm	8 x 8 x 40
Housing material		Gd Zn Al
Material of sensing face		PA 12
Degree of protection		IP65
Connection		Cable
Cable type		PVC

Electrical Data

Current type		DC
Wiring		3-Wire
switching function		normally-open
Output signal		NPN
Rated operational voltage	V	24 DC
Rated operational current	mA	200
Supply voltage	V	10...30 DC
Ripple	%	<= 10
Rated supply frequency	Hz	1000
No-load supply current	mA	<= 20 / <= 12
Off-state current	µA	<= 80
Voltage drop	V	<= 2.5 / -
Short circuit protection		yes
Protected against polarity reversal		yes

EMV

ESD / RFI / Burst / IVW
Emission

19.07.2006 / Online-Information

If not differently indicated,
all values by IEC 60947-5-2 (DIN EN60947-5-2)
Specifications subject to change

Balluff GmbH
Postfach 1160
73761 Neuhausen
Telefon (07158) 173-0
Telefax (07158) 5010

Casp System Sp. Z o.o., Puszkina 2, 43-603 Jaworzno, Polska, www.casp.pl, e-mail: biuro@casp.pl, tel/fax: +48 32 614 09 17