


cyl. D 6.5  
 Sn = 3 mm  
 DC 3-Wire  
 quasi shielded  
 sn: 3fach



PX1475



Utilization categories DC 13

Further information:  
 ■ Einbauhinweise 825356

If not differently indicated,  
 all values by IEC 60947-5-2 (DIN EN60947-5-2)  
 Specifications subject to change  
 Balluff GmbH  
 Postfach 1160  
 73761 Neuhausen  
 Telefon (07158) 173-0  
 Telefax (07158) 5010

### Common Data

Mounting		quasi shielded
Rated operating distance Sn	mm	3,0
Assured operating distance Sa	mm	0...2,4
Repeatability	%	<= 5
Function indication		yes
Ambient temperature range	°C	-25...+70

### Mechanical Data

Housing size	mm	cyl. D 6.5
Measurements BxHxT or DxT	mm	D6.5 x 60
Housing material		CuZn chrome plated
Material of sensing face		PBT
Degree of protection		IP67
Connection		Connector S49

### Electrical Data

Current type		DC
Wiring		3-Wire
switching function		normally-closed
Output signal		PNP
Rated operational voltage	V	24 DC
Rated operational current	mA	200
Supply voltage	V	10...30 DC
Rated supply frequency	Hz	1000
No-load supply current	mA	<= 12
Off-state current	µA	<= 100
Voltage drop	V	<= 2
Short circuit protection		yes
Protected against polarity reversal		yes

15.01.2007 / Online-Information

