Inductive Sensors
BES 516-350-E4-C-02

cyl. D 6.5
Sn = 2,5 mm
DC 3-Wire
unshielded



PX0343



Utilization categories DC 13

Common Data

Mounting		unshielded
Rated operating distance Sn	mm	2,5
Assured operating distance Sa	mm	0...2.0
Repeatability	%	<= 5
Hysteresis	%	1...15
Function indication		yes
Ambient temperature range	°C	-25...+70
Polution Degree		3
IEC-Code		I2B06AN1
Time delay before availability	ms	<= 10

Mechanical Data

Housing size	mm	cyl. D 6.5
Measurements BxHxT or DxT	mm	D6.5 x 30
Housing material		stainless steel
Material of sensing face		PA 12
Degree of protection		IP67
Connection		Cable
Cable type		LiYY-O

Electrical Data

Current type		DC
Wiring		3-Wire
switching function		normally-open
Output signal		NPN
Rated operational voltage	V	24 DC
Rated operational current	mA	200
Supply voltage	V	10...30 DC
Ripple	%	<= 15
Rated supply frequency	Hz	1500
No-load supply current	mA	<= 11 / <= 3
Off-state current	µA	<= 80
Voltage drop	V	<= 2.5 / -
Short circuit protection		yes
Protected against polarity reversal		yes

EMV

ESD / RFI / Burst / IVW
Emission

21.12.2006 / Online-Information

If not differently indicated,
all values by IEC 60947-5-2 (DIN EN60947-5-2)
Specifications subject to change
Balluff GmbH
Postfach 1160
73761 Neuhausen
Telefon (07158) 173-0
Telefax (07158) 5010