


ultrasonic sensor

diffuse mode sensor


RU100-Q30-LUX-H1141



Type	RU100-Q30-LUX-H1141
Ident-No.	1820205
Range	20... 100 cm
Ultrasound frequency	230 kHz
Temperature drift	0.17 % / K
Repeatability	$\geq \pm 1.5$ mm
Edge lengths of the nominal actuator	20 mm
Pass speed	1.5 m/s
Approach speed	8 m/s
Ambient temperature	0...+ 55 °C
Operating voltage	18... 35VDC
No-load current I_0	35 mA
voltage output	0... 10 V
Load resistance	$\geq 1000 \Omega$
Short-circuit protection	yes / cyclic
Reverse polarity protection	complete
Wire breakage protection	yes
Housing	rectangular, Q30
Dimensions	88 x 65 x 30 mm
Housing material	plastic, PBT-GF30-V0
Connection	connectors, M12 x 1
Degree of protection	IP65
Display 'Object detected'	LED yellow

- Operating voltage 18...35 VDC
- upper analogue range value adjustable via potentiometer
- analogue output, 0...10 V
- "object detected" indication
- synchronizable
- opening angle of sonic cone 6°

Wiring diagram



Functional principle

Ultrasonic sensors use ultrasonic waves for non-contact and wear-free detection of a large variety of objects. It does not matter whether the object is transparent or opaque, metallic or non-metallic, or of liquid, solid or powdery consistence. Environmental conditions such as spray, dust or rain hardly affect their function.

